



HBF510/HBF510S

Culinary Blenders

HBF510S



HBF510



EXPEDITOR™ family of blenders

Powerful 2.4 HP* motor lets chefs blend ingredients quickly and optimizes blending consistency

Blade design and jar shape help chefs create silky purees, creamy soups, and signature drizzles to maximize profits

Adjustable variable speed dial + pulse provide complete blending control

*input power



For more Good Thinking® visit www.hamiltonbeachcommercial.com



Dosing Cup

4 oz./118 ml capacity makes adding liquids for emulsions easy

HBF510

48 oz. (1.4 L) BPA-Free Co-Polyester Container

Lets chefs easily monitor blending consistency and is virtually unbreakable

2.4 Peak HP* Motor

Protective Brow

Directs drips away from control

Sealed Paddle Switches

Leak-resistant and easy to use

Variable Speeds

Provide complete blending control

*input power



Optimized Performance

Reduce prep time — high-performance, 2-edge stainless steel blade powers through ingredients quickly, from chunky to silky smooth

64 oz. (1.8 L) Stainless Steel Container

Perfect for hot and cold food applications

HBF510S



Durable Metal Drive Coupling



Provides long-lasting performance for uninterrupted use

Removable Jar Pad

For easy cleaning

Sure Grip™ Feet

Holds blender securely on the countertop

HBF510	SPECIFICATIONS:	HBF510S
 <p>19.3 in / 49 cm</p> <p>8.5 in / 21.5 cm</p> <p>ExpressCare WARRANTY US Only</p> <p>BPAfree in food zones</p> <p>NSF</p> <p>ETL US Intertek</p> <p>NOM</p> <p>7.5 in / 19 cm</p>	<p>Standard: unit comes with 2.4 HP motor base with 5ft / 152 cm power cord, BPA free co-polyester container</p> <p>Controls: Sealed paddle switches, variable speed dial</p> <p>Weight: 12.3 lbs / 5.6 kg (shipping)</p> <p>Warranty: 2 years parts & labor</p> <p>120 V, 60 Hz, 10 A</p> <hr/> <p>Standard: unit comes with 2.4 HP motor base with 5ft / 152 cm power cord, stainless steel container</p> <p>Controls: Sealed paddle switches, variable speed dial</p> <p>Weight: 13.9 lbs / 6.3 kg (shipping)</p> <p>Warranty: 2 years parts & labor</p> <p>120 V, 60 Hz, 10 A</p>	 <p>20.3 in / 51.5 cm</p> <p>8.5 in / 21.5 cm</p> <p>ExpressCare WARRANTY US Only</p> <p>NSF</p> <p>ETL US Intertek</p> <p>NOM</p> <p>7.5 in / 19 cm</p>