

Ref: **CH1/APN214**
Ventilated refrigerator 1400 liters 2
doors EURONORM



Your professional partner

Brand : DIAMOND



·**mm (BxDxH) :**1500x800x2040

·**T° :** -2° +8°

·**kW :**0,43

·**Volt :** 230/1N 50Hz

·**kg :**244

·**M³ :** 2,9

- 2 ventilated evaporators.
- Included: 3 grids GN 2/1 (530x650 mm) by door.
- Refrigerant R134A.
- 6 adjustable stainless steel feet.

General characteristics:

- Manufactured in stainless steel, inside AISI 304, outside AISI 44 1 (back in treated steel, gray), monocoque frame.
- Stainless steel rack and slides (anti-tilting), allowing to place the grids as ones pleases.
- Stamped interior bottom, rounded angles and corners (without roughness).
- Bottom fitted with a draining tap (big maintenance).
- Doors with ergonomic handle (no salient) and reversible (predisposition for key lock), "snap-fit" closure by magnetic joint (easy replacing without tools), hinge with stop at 100° and closure of the doors with automatic return.
- Micro-switch device, allowing the ventilator's stop, while opening the door.
- Upper panel for the accessibility of the compressor, on hinges, easy inspection.
- Refrigerated group at "tampon", tropicalized (ambient T° +43°C), and ventilated condenser.
- Ventilated evaporator(s) treated against the salt and the "coating" food acids, completely hidden (non visible).
- Refrigerant expansion by capillary.
- Electronic regulator (under closed box, tight), control front screen with blue LED.
- Intern lighting, with switch.
- Automatic defrosting of the evaporator (by electric elements), number of defrosting programmed by factory (modifiable at will).
- Condenser's automatic evaporation (warm gas).
- Polyurethane insulation without CFC (75 mm).
- The equipment is manufactured following the (CE) standards in force.

PLUS:

- Polyurethane insulation without CFC (75 mm = super insulated), less thermal dispersion, with energy savings in addition.
- Refrigerated group at "tampon", tropicalized (ambient T° +43°C).
- Exceptional services thanks to the 2 evaporators (1400 liters), allowing an uniform temperature, guaranteeing the good preserving of the products.
- Double runner slides (allowing grids and trays GN at the same time!!).
- Easy work thanks to the hinges with stop at 100° and closure of the doors with automatic recall.
- Electronic regulator (under closed box, waterproof) with HACCP functions.