## Ref: MR3/TP

## Cooling table, ventilated, 3 doors GN 1/1





**Brand: DIAMOND** 





·mm (BxDxH) :1800x700xh880/900

 $\cdot \mathbf{T}^{\circ} : 0^{\circ} + 8^{\circ}$ 

·**kW** :0,4

·Volt: 230/1N 50-60Hz

 $\cdot$ **kg**: 148  $\cdot$ **M**<sup>3</sup>: 1,6

- Included: 3 grids (325x535 mm), with slides.
- 4 adjustable stainless steel feet.
- Compact structure, inside and outside manufactured in (food) stainless steel, upper top (40 mm).
- Stamped inside bottom with draining cap (high maintenance), rounded angles and corners (without bumps), racks and slides (anti-swinging) in stainless steel.
- Reversible doors, with built-in handles (not salient), magnetic joint (easy replacement, without tools), hinge with automatic return (blocking at 90°), 1 grid by door.
- Compressor group (climatic class +38°C), ventilated condenser, placed on the left side, frontal accessibility (panel on hinges), on "removable" slides, easy cleaning and maintenance.
- Refrigerant expansion R134A by capillary.
- Ventilated evaporator (oversized), treated against the salt and the food acids, completely hidden (not visible).
- Programmable electronic regulator, display on front with blue LED.
- Automatic defrosting by reversal of cycle (programmable as one pleases), automatic evaporation of the condenser (by warm gas).
- Polyurethane insulation without CFC.
- Adjustable stainless steel feet.
- The equipment is manufactured following the (CE) standards in force.