

## Tabel-Top-Model EST 10 Series

## Vacuum-Packing-Machines

### **LC and LS Features**

- Vacuum-chamber and casing complete stainless steel
- Automatic adaptation of the sealing intensity
- Easy removable sealing bar
- Constructed for easy service work
- Automatic process with lid opening
- Extra-clean design of components such as sealingbar, counterbar hinges
- Soft Air reventilation of the chamber
- Acrylicglas lid for observation of packing
- Complete set of filler plates
- Optional: gas flushing device
- Vacuum detection (no Time Controls)
- Oil-regeneration program

### **Additional LS Features**

- Sensor-microprocessor control with LCD display and „easy clean“ touch panel Senso Touch
- 10 individual storeable programs even for interrupted cycles + 2 special programs
- Standard already prepared for „Green Vac“ with exact measurement of vacuum



EST 10 LS dome lid (K)



EST 10 LC

Technical Data		EST 10 / EST 10 K	
■ Chamber size inside	height depth width	110 mm 350 mm 305 mm	165 mm 350 mm 305 mm
■ External dimensions	height depth width	350 mm 535 mm 365 mm	415 mm 535 mm 365 mm
■ Weight		58 kg	
■ Length of sealing-bar		300 mm	
■ Packaging performance		1 to 3 / min.	
■ Vacuum pump standard		21 m <sup>3</sup> / h	
■ Electrical supply standard		LC: 230V / 1 or on request LS: 400V / 3 or on request	

*Technical modifications reserved*